

# CAUTION!!!

DO NOT OVER TIGHTEN EZ READ TIRE CAPS  
PLEASE FOLLOW INSTALLATION INSTRUCTIONS



Here is a link to a YouTube video that demonstrates how easy it is to install the EZ read Tire caps.

<https://www.youtube.com/watch?v=KeOxgqBt9aI>

(The EZ Read Tire Cap functions by monitoring your PSI – if you over tighten the tire stem will become fully depressed, resulting in a flat tire. Installation is quick and easy following simple instructions.)

**INSTALLATION** – Remove original tire cap – Place new EZ READ TIRE CAP on valve stem, turning clockwise \*\*ONLY HAND TIGHTEN UNTIL YOU HEAR THE AIR STOP HISSING OUT THEN TURN ONE HALF TURN MORE AND STOP\*\* - if you over tighten, air will leak out and your tire will go flat – Green is inflated properly.

30-Day Money Back Guarantee (Less P&H). Please return (postage pre-paid) to address listed below. Please be sure to include your complete name, address, daytime telephone number and email address inside the package when returning your item.

EZ Read Tire Cap for STANDARD TIRE STEM only – will not function on specialty tires or non-standard tire stem.

If you have stainless steel tire stems (especially if you live in climate w/snow and road salt/sand) you should periodically remove the EZ Read Tire Cap during winter season and clean both stem and cap.

## WARRANTY

This product has a warranty to be free of manufacturing defects for a period of one year from date of purchase. If found to be defective, please return the product with dated proof of purchase for immediate replacement.

This warranty is limited to the replacement of the product only and does not extend to any incremental cost incurred should the product fail. In no case shall liability exceed the purchase price. This warranty gives you specific rights, which may vary from state to state.

CLC International Inc.

6287 State Rd 15  
Leesburg, IN 46538  
574-253-6177

[kkeeling@clcinternationalinc.com](mailto:kkeeling@clcinternationalinc.com)  
[www.clcinternationalinc.com](http://www.clcinternationalinc.com)